

89MDA

Wall Mount Inflator



The MDA model is a lightweight, impact-resistant tyre inflator designed for both indoor and outdoor use in workshops and service centres. It delivers safe, accurate, and reliable inflation across all applications — from trolleys and bicycles to cars and trucks.

It can be operated in different pressure measurements including PSI or kPa. Features include a 'Flat Tyre Only' button for low-pressure starts, a 10m air hose kit with hook, and nitrogen compatibility.



Features



Durable & Compact

Lightweight, impact-resistant enclosure with an IP66 rating for protection against splashes and dust.



Safe & Accurate

Designed with user safety in mind, this system delivers precise results with minimal effort



Easy Installation

Designed for versatility, this unit includes a 10m inlet hose and hook for user convenience.



Nitrogen Compatible

Engineered for flexibility, this system is fully compatible with both air and nitrogen inflation.



Multiple Applications

Multi-purpose unit suitable for trolleys, cars, trucks and bicycles. With with selectable PSI or kPa units.

Optional Item



Core Removal Tool Faster Inflation

When used with the Core Removal Tool, it provides a faster and controlled inflation process (optional).

Technical Data

Wall Mount Inflator



Construction

Outer Shell	High Impact Polycarbonate IP66 rating
-------------	---------------------------------------

Electrical

Power	220 ~ 240VAC (Optional 12VDC)
-------	-------------------------------

Specifications

Measurement	psi kPa
Range	5 ~ 145psi 35 ~ 1000kPa
Accuracy ±	± 0.5% Full Scale

Included Parts



61.0001	Hose Assy Standard Airtec Grey 10m
---------	------------------------------------



13.0904	Hose hook P/C Grey
---------	--------------------

Warranty

Manufacturer's Warranty	For warranty information please visit our website <u>www.airteccorporation.com</u>
-------------------------	--
