

89TR5 - Nitrogen Trolley Inflator

89TR5-1001



89TR5-1001

89TR5 - Nitrogen Trolley Inflator

The TR5 offers a convenient mobile solution for filling tyres with Nitrogen. It is ideal for workshops, tyre stores, fleets, lube shops and auto dealerships, providing safe, accurate and reliable Nitrogen tyre inflation for customers.

The rugged unit can inflate up to 5 tyres at once. Simply connect the unit to a fixed Nitrogen source such as a generation system or fixed bottle supply. The inflation process starts automatically once the hoses are connected to the tyres. The hoses are fitted with clip-on closed chucks allowing the technician to attend to other duties during the inflation process. The beeper indicates when the cycle is completed.

The integrated accessory box provides storage compartments for chucks and other components such as valve cores and caps. The TR5 is supplied with high capacity NiMH battery to power the unit; typically it only requires to be charged every few days. The battery life is extended by an automatic power off function.



89TR5 - Nitrogen Trolley Inflator

89TR5-1001



RAL 9010 IP40 CE



Features

- Automatic purging program(N2P)
- Adjustable over pressure settings (OPS)
- Accurate and easy to use; inflate up to 5 tyres at once
- Rugged and durable design with solid rubber tyres
- Auto power off function, charger and NiMH battery supplied
- Suits direct Nitrogen supply from an N² generator

Specifications

Construction	Powder coated steel
Degree of Protection	IP40
Power	12VDC
Measurement	Psi kPa bar
Range	5 - 145 psi 35 - 1000 kPa 0.3 - 10 bar
Accuracy ±	± 0.5% Full Scale

Included Accessories

	91.5055	Air Chuck SB Clip On Straight Closed 1/4 BSPM
	61.0338	Hose Assy Mignon Rubber Black 8m w 91.5055
	46.0010	Battery Pack TRS Airtec White 12V

Optional Accessories

	97.1110	Battery Kit TRS Replacement Pack
	49.1001	Regulator Type 50 Nitrogen 1000kPa

